



P.O. Box 8068  
 Pine Bluff, AR 71611  
 P: (870)-535-4753 (800)-238-5042  
 F: (870)-535-4843  
 www.strongmfg.com

**Strong Manufacturing Product Testing**

The following information is based upon Strong Manufacturing staff performing various test with the material provided by the provider listed below. All test and usage will be conducted at the facility of Strong.

**Material Provider:** Stone Edge Surfaces

**Material Tested:** Pro-Bond

Date	<u>11/18/2020</u>	Time to Unload Mixer	<u>26sec</u>
Strong Mfg. Equipment	<u>FloorMate80</u>	Size of Material Hose	<u>1.25"</u>
Ambient Temperature	<u>68</u>	Length of Hose	<u>50'</u>
Humidity	<u>25%</u>	Test Method	<u>Double Drum Mixer with Progressive Cavity Pump</u>
Product Name	<u>Pro-Bond</u>	Pump Hydraulic Pressure	<u>800PSI</u>
Bag Size	<u>50lb</u>	Pump Back Pressure	<u>0PSI</u>
Bags per Mix	<u>2</u>	Flow Rate	<u>20GPM Variable</u>
Water Temperture	<u>64</u>	Density of Pumped Material	<u>8oz (2x2)</u>
Water per Mix	<u>2.25gal</u>	Slump Test of Material Pumped	
Mixer Hydraulic Pressure to Mix	<u>500</u>	1 Day Compressive Strength	
Mix Time	<u>2:00</u>	3 Day Compressive Strength	
Density of Material Out of Mixer	<u>N/A</u>	7 Day Compressive Strength	
Slump Test of Material Out of Mixer	<u>N/A</u>	28 Day Compressive Strength	

**Notes:**

Jesse Downs  
 Performed By

11/19/2020  
 Date